Dartron Salem, Oregon 97309 Issuing Entity:
Dartron Industries, Inc

P. O. Box 13114

Phone: 503-362-2341 Fax: 503-362-2536

www.dartronrides.com

Bulletin # PI-04020K-02

Release Date: February 27, 2004

Effective Date: February 26, 2004

Supercedes: N/A

Completion Date: April 1, 2004

Page 1 of 2

PRODUCT IMPROVEMENT

Ride Manufacturer:	Dartron Industries, Inc.	Affected Production Dates:	All
Ride Name: Cliff Hanger		Affected Serial #'s	All
Model # All			

Abstract of Issue: Dartron has designed a more robust car hanger for the Cliff Hanger ride. The more robust car hanger locates the gussets on the front and rear faces of the square and round tubes. At one location in the car transport rack this gusset configuration creates an interference with the car transport rack. The only location where this interference is experienced is the third position in on both the driver and passenger side car transport racks. To be able to transport the more robust car hanger in the third position in either transport rack a modification must be made to the rack.

Reason for release: To inform Cliff Hanger owners who receive the more robust car hanger of the interference problem and to provide information on the procedure to be followed to correct the interference.

Action to be taken:

- 1. Dartron will provide a template to be used to identify the material that should be removed from the car transport rack.
- 2. Place the template on the web of a transport rack. See Page two.
- 3. Align the hole in the template with the hole in the web and align the bottom point of the template with the similar point on the web. See Page two.
- 4. Mark the material to be removed.
- 5. Material can be removed by use of a grinder or by either an Oxygen Acetylene or Plasma arch cutting system.
- 6. The edge that is cut must be ground or sanded smooth to remove any slag or gouging from the cutting process.
- 7. A clean smooth surface of the cut area is essential to avoid stress risers that, over time, could result in cracking.

